

Certificate of Product Ratings

AHRI Certified Reference Number : 204340356

Date : 08-08-2019

Model Status : Active

Brand Name : Daikin

Model Designation : DDA1-0404 - 2539

Rated as follows in accordance with the latest edition of ANSI/AHRI Standard 1350 (I-P) - Mechanical Performance Rating of Central Station Air-handling Unit Casings and subject to rating accuracy by AHRI-sponsored, independent, third party testing:

Casing Deflection Rating Class (Positive) : CD3

Casing Deflection Rating Class (Negative) : CD3

Casing Air Leakage Class (Positive) : CL3

Casing Air Leakage Class (Negative) : CL3

Thermal Transmittance Class with Leakage : CT4

Thermal Transmittance Class without Leakage : CT4

Thermal Bridging Class : CB3

Equipment Line Name : DDA

Wall Construction : Double Skin Polyurethane foam and insulation panel

Insulation Type : Polyurethane foam

Insulation Thickness : 1 inch

Assembly Method : Frame AHU with Clip locking method

Range of Exterior Air Tunnel Cross- Sectional Areas ft² : 5.9-129.6

Casing Design Pressure (Positive) : 6.0

Casing Design Pressure (Negative) : 6.0

†"Active" Model Status are those that an AHRI Certification Program Participant is currently producing AND selling or offering for sale; OR new models that are being marketed but are not yet being produced."Production Stopped" Model Status are those that an AHRI Certification Program Participant is no longer producing BUT is still selling or offering for sale.
Ratings that are accompanied by WAS indicate an involuntary re-rate. The new published rating is shown along with the previous (i.e. WAS) rating.

DISCLAIMER

AHRI does not endorse the product(s) listed on this Certificate and makes no representations, warranties or guarantees as to, and assumes no responsibility for, the product(s) listed on this Certificate. AHRI expressly disclaims all liability for damages of any kind arising out of the use or performance of the product(s), or the unauthorized alteration of data listed on this Certificate. Certified ratings are valid only for models and configurations listed in the directory at www.ahridirectory.org.

TERMS AND CONDITIONS

This Certificate and its contents are proprietary products of AHRI. This Certificate shall only be used for individual, personal and confidential reference purposes. The contents of this Certificate may not, in whole or in part, be reproduced; copied; disseminated; entered into a computer database; or otherwise utilized, in any form or manner or by any means, except for the user's individual, personal and confidential reference.

CERTIFICATE VERIFICATION

The information for the model cited on this certificate can be verified at www.ahridirectory.org, click on "Verify Certificate" link and enter the AHRI Certified Reference Number and the date on which the certificate was issued, which is listed above, and the Certificate No., which is listed at bottom right.

©2019 Air-Conditioning, Heating, and Refrigeration Institute



we make life better™

CERTIFICATE NO.:

132097255825164193

Certificate of Product Ratings

AHRI Certified Reference Number : 204340357

Date : 08-08-2019

Model Status : Active

Brand Name : Daikin

Model Designation : DDA2-0404 - 2539

Rated as follows in accordance with the latest edition of ANSI/AHRI Standard 1350 (I-P) - Mechanical Performance Rating of Central Station Air-handling Unit Casings and subject to rating accuracy by AHRI-sponsored, independent, third party testing:

Casing Deflection Rating Class (Positive) : CD2

Casing Deflection Rating Class (Negative) : CD2

Casing Air Leakage Class (Positive) : CL2

Casing Air Leakage Class (Negative) : CL2

Thermal Transmittance Class with Leakage : CT3

Thermal Transmittance Class without Leakage : CT3

Thermal Bridging Class : CB3

Equipment Line Name : DDA

Wall Construction : Double Skin Polyurethane foam and insulation panel

Insulation Type : Polyurethane foam

Insulation Thickness : 2 inch

Assembly Method : Frame AHU with Clip locking method

Range of Exterior Air Tunnel Cross- Sectional Areas ft² : 5.9-129.6

Casing Design Pressure (Positive) : 8.0

Casing Design Pressure (Negative) : 8.0

†"Active" Model Status are those that an AHRI Certification Program Participant is currently producing AND selling or offering for sale; OR new models that are being marketed but are not yet being produced."Production Stopped" Model Status are those that an AHRI Certification Program Participant is no longer producing BUT is still selling or offering for sale.
Ratings that are accompanied by WAS indicate an involuntary re-rate. The new published rating is shown along with the previous (i.e. WAS) rating.

DISCLAIMER

AHRI does not endorse the product(s) listed on this Certificate and makes no representations, warranties or guarantees as to, and assumes no responsibility for, the product(s) listed on this Certificate. AHRI expressly disclaims all liability for damages of any kind arising out of the use or performance of the product(s), or the unauthorized alteration of data listed on this Certificate. Certified ratings are valid only for models and configurations listed in the directory at www.ahridirectory.org.

TERMS AND CONDITIONS

This Certificate and its contents are proprietary products of AHRI. This Certificate shall only be used for individual, personal and confidential reference purposes. The contents of this Certificate may not, in whole or in part, be reproduced; copied; disseminated; entered into a computer database; or otherwise utilized, in any form or manner or by any means, except for the user's individual, personal and confidential reference.

CERTIFICATE VERIFICATION

The information for the model cited on this certificate can be verified at www.ahridirectory.org, click on "Verify Certificate" link and enter the AHRI Certified Reference Number and the date on which the certificate was issued, which is listed above, and the Certificate No., which is listed at bottom right.

©2019 Air-Conditioning, Heating, and Refrigeration Institute



we make life better™

CERTIFICATE NO.:

132097256215789991

Certificate of Product Ratings

AHRI Certified Reference Number : 204340358

Date : 08-08-2019

Model Status : Active

Brand Name : Daikin

Model Designation : DDA2TB-0404 - 2539

Rated as follows in accordance with the latest edition of ANSI/AHRI Standard 1350 (I-P) - Mechanical Performance Rating of Central Station Air-handling Unit Casings and subject to rating accuracy by AHRI-sponsored, independent, third party testing:

Casing Deflection Rating Class (Positive) : CD2

Casing Deflection Rating Class (Negative) : CD2

Casing Air Leakage Class (Positive) : CL2

Casing Air Leakage Class (Negative) : CL2

Thermal Transmittance Class with Leakage : CT2

Thermal Transmittance Class without Leakage : CT2

Thermal Bridging Class : CB2

Equipment Line Name : DDA

Wall Construction : Double Skin Polyurethane foam and insulation panel

Insulation Type : Polyurethane foam

Insulation Thickness : 2 inch

Assembly Method : Frame AHU with Clip locking method

Range of Exterior Air Tunnel Cross- Sectional Areas ft² : 5.9-129.6

Casing Design Pressure (Positive) : 8.0

Casing Design Pressure (Negative) : 8.0

†"Active" Model Status are those that an AHRI Certification Program Participant is currently producing AND selling or offering for sale; OR new models that are being marketed but are not yet being produced."Production Stopped" Model Status are those that an AHRI Certification Program Participant is no longer producing BUT is still selling or offering for sale.
Ratings that are accompanied by WAS indicate an involuntary re-rate. The new published rating is shown along with the previous (i.e. WAS) rating.

DISCLAIMER

AHRI does not endorse the product(s) listed on this Certificate and makes no representations, warranties or guarantees as to, and assumes no responsibility for, the product(s) listed on this Certificate. AHRI expressly disclaims all liability for damages of any kind arising out of the use or performance of the product(s), or the unauthorized alteration of data listed on this Certificate. Certified ratings are valid only for models and configurations listed in the directory at www.ahridirectory.org.

TERMS AND CONDITIONS

This Certificate and its contents are proprietary products of AHRI. This Certificate shall only be used for individual, personal and confidential reference purposes. The contents of this Certificate may not, in whole or in part, be reproduced; copied; disseminated; entered into a computer database; or otherwise utilized, in any form or manner or by any means, except for the user's individual, personal and confidential reference.

CERTIFICATE VERIFICATION

The information for the model cited on this certificate can be verified at www.ahridirectory.org, click on "Verify Certificate" link and enter the AHRI Certified Reference Number and the date on which the certificate was issued, which is listed above, and the Certificate No., which is listed at bottom right.

©2019 Air-Conditioning, Heating, and Refrigeration Institute



we make life better™

CERTIFICATE NO.:

132097256670165820